

SINGLE STOREY 2.7m TIMBER STUD CONCRETE GROUND FLOOR

CONSTRUCTION DETAILS

In Accordance with NZS 3604:1999

WALL BRACING DESIGN

 Design the wall bracing system for a "Heavy Cladding" system as defined by NZS 3604:1999

DESIGN ASSUMPTIONS

- Maximum snow load : 0.5kPa
- Utimate ground bearing of 300kPa in accordance with NZS 3604:1999
 Well drained soil conditions in accordance with NZS 3604:1999

NOTE: ALL BUILDING MUST COMPLY WITH NZS 3604: 1999 AND THE NEW ZEALAND BUILDING CODE

Technical Biodainer: This information is intended solely as a guide for use of Village Stone products. Before using Village Stone products you should ensure that the product is suitable for use in the specific application. Nothing in this information constitutes a statement of fitness for particular purpose - appropriate expert advice should always be obtained. Village Stone product you will be information with non-Village Stone product. Product is suitable for use in the specific application. Nothing in this information constitutes a statement of fitness for particular purpose - appropriate expert advice should always be obtained. Village Stone product you will be suitable for use in the specific application. Nothing in this information constitutes a statement of fitness for particular purpose - appropriate expert advice should always be obtained. Village Stone product you will be suitable for use in the specific application. Nothing in this information constitutes a statement of fitness for particular purpose - appropriate expert advice should always be obtained. Village Stone product you will be suitable for use of the specific application. We have a suitable for use of the specific application. As the specific application is intended as a specific application. As the specific application is intended as a specific application. As the specific application is intended as a specific application.



VILLAGE STONE VENEER DETAILS Option 2: Single Storey 2.7m Stud scale 1:20

SK2